

ROTARY DRILLING AND VIBRATOR, MUD DELIVERY AND CEMENT HOSES

XTREME™ ROTARY VIBRATOR 7500 GRADE E



HIGH PRESSURE OILFIELD HOSE



APPLICATION

Gates Black Gold™ XTreme™ hose product family is specifically designed for today's demanding drilling conditions, and meets or exceeds FSL1 industry performance standards. The UltraBration hose cover material resists external abrasion, chemical and U/V attack.

TEMPERATURE (-20°C to +82°C)(-4°F to +180°F)

CONSTRUCTION Tube Type C3 (Modified Nitrile)

Reinforcement Multiple layers of textile fabric cords, steel cables and special rubber materials

Cover UltraBration (Nitrile)

STANDARDS API Specification 7K FSL 1 (6th Edition), ISO 14693

COUPLINGS Swaged Couplings



ID		OD		WORKING PRESSURE		BURST PRESSURE		MBR		WEIGHT		MAX HOSE LENGTH
inch	mm	inch	mm	bar	psi	bar	psi	inch	mm	kg/ft	lb/ft	ft
3 1/2	89	6.15	156	517	7500	1290	18750	54	1372	11	24	90

Gates Corporation is a leading manufacturer of application-specific fluid power and power transmission solutions. At Gates, we are driven to push the boundaries of materials science to engineer products that continually exceed expectations.